

Drive shaft identification

| W Standard drive shaft | | WWE80° Wide angle drive shaft | | | WWE50° Wide angle drive shaft | | | |
|------------------------|---------------|-------------------------------|----------------|-------|-------------------------------|----------------|-------|------------|
| Series | Cross Journal | Yoke | Profile Tubing | Guard | Guard Cone | Profile Tubing | Guard | Guard Cone |
| W 2000 | | | | | | | | |
| W 2100 | | | | | | | | |
| W 2102 | | | | | | | | |
| W 2200 | | | | | | | | |
| WWE WWZ 2250 | | | | | | | | |
| WWE WWZ 2280 | | | | | | | | |
| W 2300 | | | | | | | | |
| WWE WWZ 2350 | | | | | | | | |
| WWE WWZ 2380 | | | | | | | | |
| W 2400 | | | | | | | | |
| WWE WWZ 2450 | | | | | | | | |
| WWE WWZ 2480 | | | | | | | | |
| W 2500 | | | | | | | | |
| WWE WWZ 2580 | | | | | | | | |
| W 2600 | | | | | | | | |
| W 2700 | | | | | | | | |

* GA = Coated surface for WWE/WWZ

** GE Special Outer Profile for Coated Inner Profile

*** H = Hardened

| | | | | | | |
|-----------------------|--|--------------|--------------|--------------|----------------|--------------|
| Groove for guard ring | | SQSD05: D=47 | SQSD15: D=58 | SQSD25: D=70 | SQSD25/I: D=70 | SQSD35: D=90 |
|-----------------------|--|--------------|--------------|--------------|----------------|--------------|

Drive shaft identification types to be discontinued

(Spare parts only, not available as complete shaft)

| Series | Cross Journal | Yoke | Replaced by Series | Profile Tubing | PTO Guards | Guards Cones |
|--------------|---------------|------|--------------------|----------------|------------|--------------|
| W 2101 | | | W 2102 | | | |
| W I | | | W 2300 | | | |
| W II | | | W 2400 | | | |
| W 220 | | | W 2400 | | | |
| WWE WWZ 2270 | | | WWE WWZ 2280 | | | |
| WWE WWZ 2370 | | | WWE WWZ 2380 | | | |
| WWE WWZ 220 | | | WWE WWZ 2480 | | | |

* GA = Coated Shaft for WWE/WWZ

GE Special Outer Profile
for Cones Inner Profile

SC04/14/24/34 Has been Replaced
by SC05/15/25/35

Tractor spare profile sizes:

| | |
|-------------------|--------------------|
| <p>1 3/8" (6)</p> | <p>1 3/8" (21)</p> |
| <p>1 3/4" (6)</p> | <p>1 3/4" (20)</p> |



Repairs only original Walterscheid branded shafts

